



### Dimension Plank

<b>DIMENSIONS</b>	1200 mm x 150 mm
<b>THICKNESS</b>	10 mm
<b>TOP LAYER</b>	3.00 mm

### Dimension Pack

<b>PACK LENGTH</b>	1210 mm
<b>PACK WIDTH</b>	160 mm
<b>PACK THICKNESS</b>	120 mm
<b>PACK WEIGHT</b>	12,50 kg
<b>PLANCKS / PACK</b>	12
<b>M<sup>2</sup>/PACK</b>	2,16 m <sup>2</sup>

### Dimension Pallet

<b>PALLET LENGTH</b>	1250mm
<b>PALLET WIDTH</b>	1005 mm
<b>PALLET HEIGHT</b>	1005 mm
<b>PALLET WEIGHT</b>	700,00kg
<b>PACKS / PALLET</b>	56
<b>M<sup>2</sup>/PALLET</b>	121,00 m <sup>2</sup>

## Features


### Top layer

<b>WOOD SPECIES</b>	Oak
<b>LATIN NAME</b>	Quercus Robur
<b>CATEGORY</b>	CLASSIC: A rustic floor with knots and slight variations in colour, no core defects and occasional traces of sapwood.
<b>CONSTRUCTION</b>	2-ply
<b>THICKNESS</b>	3,00 mm
<b>STRIPS</b>	1
<b>CUTTING METHOD</b>	sawn veneer
<b>BEVEL</b>	Two long sides (0.50 mm)
<b>FINISHING</b>	Unfinished
<b>STRUCTURE</b>	Smooth

### Composition of frame

<b>TYPE</b>	Poplar framework
<b>WOOD TYPE BASIS</b>	Poplar
<b>CONSTRUCTION BASIS</b>	2-layer (intermediate layer + balancer)
<b>TOTAL THICKNESS OF FRAME</b>	7,00 mm
<b>ADHESIVE</b>	Cross glued (Casco)

### Steps

<b>SYSTEM</b> Tongue and groove system 	<b>APPLICATION</b> Light household use Normal household use Moderate commercial use Normal commercial use Intensive commercial use	<b>UNDERFLOOR HEATING</b> Yes <b>RE-SANDABLE</b> Yes <hr/> More info on <a href="http://www.lalegno.be">www.lalegno.be</a> "All about parquet"
--	---	---