



**Size Board**

|                            |        |
|----------------------------|--------|
| <b>LENGTH</b>              | 540 mm |
| <b>WIDTH</b>               | 90 mm  |
| <b>TOTAL THICKNESS</b>     | 15 mm  |
| <b>THICKNESS TOP LAYER</b> | 4 mm   |

**Size Pack**

|                           |                     |
|---------------------------|---------------------|
| <b>PACK LENGTH</b>        | 600 mm              |
| <b>PACK WIDTH</b>         | 190 mm              |
| <b>PACK THICKNESS</b>     | 125 mm              |
| <b>PACK WEIGHT</b>        | 8 kg                |
| <b>LAYERS/PACK</b>        | 16                  |
| <b>M<sup>2</sup>/PACK</b> | 0.78 m <sup>2</sup> |

**Size Pallet**

|                             |                     |
|-----------------------------|---------------------|
| <b>LENGTH PALLET</b>        | 1810 mm             |
| <b>WIDTH PALLET</b>         | 1000 mm             |
| <b>HEIGHT PALLET</b>        | 870 mm              |
| <b>WEIGHT PALLET</b>        | 655 kg              |
| <b>PACKS/PALLET</b>         | 80                  |
| <b>M<sup>2</sup>/PALLET</b> | 62.4 m <sup>2</sup> |

**Characteristics**

**Top layer**

|                            |                                  |
|----------------------------|----------------------------------|
| <b>WOOD SPECIES</b>        | Oak                              |
| <b>LATIN NAME</b>          | Quercus Robur                    |
| <b>GRADE</b>               | CLASSIC                          |
| <b>CONSTRUCTION</b>        | 2-layer                          |
| <b>THICKNESS TOP LAYER</b> | 4 mm                             |
| <b>STRIPS</b>              | 1 strip                          |
| <b>CUTTING METHOD</b>      | Sawn veneer                      |
| <b>BEVEL</b>               | Micro bevel Four sides (0,50 mm) |
| <b>COLOUR FINISH</b>       | Unfinished                       |
| <b>SURFACE STRUCTURE</b>   | Smooth                           |

**Composition of the support**

|                                |                      |
|--------------------------------|----------------------|
| <b>SUPPORT TYPE</b>            | Multiplex support    |
| <b>WOOD SPECIES SUPPORT</b>    | Mixed Light Hardwood |
| <b>SUPPORT CONSTRUCTION</b>    | Multiplex (8 layers) |
| <b>TOTAL THICKNESS SUPPORT</b> | 11 mm                |
| <b>ADHESION</b>                | Crosswise (Casco)    |

**Installation**

**SYSTEM**

Tongue and groove system



**APPLICATIONS**

Light household use  
 Moderate commercial use  
 Take the necessary precautions for use in wet areas  
 Normal commercial use  
 Normal household use  
 Intensive commercial use

**UNDERFLOOR HEATING**

Yes

**RESANDABLE**

Resandable