



**Size Board**

<b>LENGTH</b>	1900 mm
<b>WIDTH</b>	240 mm
<b>TOTAL THICKNESS</b>	15 mm
<b>THICKNESS TOP LAYER</b>	4 mm
<b>PLANK QUANTITY</b>	Min. 5 Pl. x 1900 mm

**Size Pack**

<b>PACK LENGTH</b>	1910 mm
<b>PACK WIDTH</b>	250 mm
<b>PACK THICKNESS</b>	100 mm
<b>PACK WEIGHT</b>	24 kg
<b>LAYERS/PACK</b>	6
<b>M<sup>2</sup>/PACK</b>	2.74 m <sup>2</sup>

**Size Pallet**

<b>LENGTH PALLET</b>	1930 mm
<b>WIDTH PALLET</b>	1000 mm
<b>HEIGHT PALLET</b>	1120 mm
<b>WEIGHT PALLET</b>	975 kg
<b>PACKS/PALLET</b>	40
<b>M<sup>2</sup>/PALLET</b>	109.6 m <sup>2</sup>

**Characteristics**

**Top layer**

<b>WOOD SPECIES</b>	Oak
<b>LATIN NAME</b>	Quercus Mongolica
<b>GRADE</b>	AB
<b>CONSTRUCTION</b>	3-layer
<b>THICKNESS TOP LAYER</b>	4 mm
<b>STRIPS</b>	1 strip
<b>CUTTING METHOD</b>	Sawn veneer
<b>BEVEL</b>	Two long sides (0,75 mm)
<b>COLOUR FINISH</b>	Unfinished
<b>SURFACE STRUCTURE</b>	Smooth

**Composition of the support**

<b>SUPPORT TYPE</b>	Poplar support and backing
<b>WOOD SPECIES SUPPORT</b>	Poplar
<b>SUPPORT CONSTRUCTION</b>	2-layer (Support, balancer)
<b>TOTAL THICKNESS SUPPORT</b>	11 mm
<b>ADHESION</b>	Crosswise (Casco)

**Installation**

**SYSTEM**

G5 Click system



**APPLICATIONS**

- Light household use
- Moderate commercial use
- Normal commercial use
- Normal household use
- Intensive commercial use

**UNDERFLOOR HEATING**

Yes

**RESANDABLE**

Resandable