



Size Board

LENGTH	2200 mm
WIDTH	260 mm
TOTAL THICKNESS	15 mm
THICKNESS TOP LAYER	4 mm
PLANK QUANTITY	Min. 3 Pl. x 2200 mm

Size Pack

PACK LENGTH	2210 mm
PACK WIDTH	270 mm
PACK THICKNESS	70 mm
PACK WEIGHT	20 kg
LAYERS/PACK	4
M²/PACK	2.29 m ²

Size Pallet

LENGTH PALLET	2230 mm
WIDTH PALLET	1080 mm
HEIGHT PALLET	820 mm
WEIGHT PALLET	815 kg
PACKS/PALLET	40
M²/PALLET	91.6 m ²

Characteristics

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Mongolica
GRADE	CLASSIC
CONSTRUCTION	3-layer
THICKNESS TOP LAYER	4 mm
STRIPS	1 strip
CUTTING METHOD	Sawn veneer
BEVEL	Distressed bevel (0,50 mm) to short and long sides
COLOUR FINISH	Smoked Unfinished
SURFACE STRUCTURE	Antique effect

Composition of the support

SUPPORT TYPE	Poplar support and backing
WOOD SPECIES SUPPORT	Poplar
SUPPORT CONSTRUCTION	2-layer (Support, balancer)
TOTAL THICKNESS SUPPORT	11 mm
ADHESION	Crosswise (Casco)

Installation

SYSTEM

G5 Click system



APPLICATIONS

Light household use
Moderate commercial use
Normal commercial use
Normal household use
Intensive commercial use

UNDERFLOOR HEATING

Yes

RESANDABLE

The thickness of the upper layer allows resanding the floor, but this may influence the floor structure.